WEIGHT AND BALANCE / TOLD
C-172P

C-172P	N-				
DATE:		SORTIE #			
PIC:					

	WEIGHT (LBS)	ARM (IN)	MOMENT (IN/LBS)
AIRCRAFT BASIC EMPTY WEIGHT			
USABLE FUEL (40 GAL X 6 LBS/GAL)	+	X 48.0	+
PILOT AND COPILOT	+	X 37.0	+
REAR PASSENGERS	+	X 73.0	+
BAGGAGE AREA 1 (120 LBS MAX)	+	X 95.0	+
BAGGAGE AREA 2 (50 LBS MAX)	+	X 123.0	+
START, TAXI, RUNUP FUEL	-7.0	X 48.0	-336
TAKEOFF WEIGHT / CG / MOMENT			
MISSION FUEL (10 GAL X 6 LBS X #HRS)	-	X 48.0	-
LANDING WEIGHT / CG / MOMENT			

CG (IN) = SUM OF MOMENTS / SUM OF WEIGHTS

WRITE TAKEOFF AND LANDING CG IN ARM COLUMN ABOVE, MARK ON DIAGRAM BELOW



WEIGHT AND BALANCE / TOLD
C-172P

TAKEOFF DISTANCE
MAXIMUM WEIGHT 2400 LBS
SHORT FIELD

CONDITIONS:
Flaps 10°
Full Throttle Prior to Brake Release
Paved, Level, Dry Runway
Zero Wind

NOTES:
1. Short field technique as specified in Section 4.
2. Prior to takeoff from fields above 3000 feet elevation, the mixture should be leaned to give maximum RPM in a full throttle, static runup.
3. Decrease distances 10% for each 9 knots headwind. For operation with tailwinds up to 10 knots, increase distances by 10% for each 2 knots.
4. For operation on a dry, grass runway, increase distances by 15% of the "ground roll" figure.

WEIGHT LBS	TAKEOFF SPEED KIAS		PRESS ALT FT	0°C		10°C		20°C		30°C		40°C	
	LIFT OFF	AT 50 FT		GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS
2400	51	56	S.L.	795	1460	860	1570	925	1685	995	1810	1065	1945
			1000	875	1605	940	1725	1015	1860	1090	2000	1170	2155
			2000	960	1770	1035	1910	1115	2060	1200	2220	1290	2395
			3000	1055	1960	1140	2120	1230	2295	1325	2480	1425	2685
			4000	1165	2185	1260	2365	1355	2570	1465	2790	1575	3030
			5000	1285	2445	1390	2660	1500	2895	1620	3160	1745	3455
			6000	1425	2755	1540	3015	1665	3300	1800	3620	1940	3990
			7000	1580	3140	1710	3450	1850	3805	2000	4220	- - -	- - -
			8000	1755	3615	1905	4015	2060	4480	- - -	- - -	- - -	- - -

Figure 5-5. Takeoff Distance (Sheet 1 of 2)

C-172P	N-
TEMP	
PA	
TO DIST	
LND DIST	

LANDING DISTANCE
SHORT FIELD

CONDITIONS:
Flaps 30°
Power Off
Maximum Braking
Paved, Level, Dry Runway
Zero Wind

NOTES:
1. Short field technique as specified in Section 4.
2. Decrease distances 10% for each 9 knots headwind. For operation with tailwinds up to 10 knots, increase distances by 10% for each 2 knots.
3. For operation on a dry, grass runway, increase distances by 45% of the "ground roll" figure.
4. If a landing with flaps up is necessary, increase the approach speed by 7 KIAS and allow for 35% longer distances.

WEIGHT LBS	SPEED AT 50 FT KIAS	PRESS ALT FT	0°C		10°C		20°C		30°C		40°C	
			GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS	GRND ROLL FT	TOTAL FT TO CLEAR 50 FT OBS
2400	61	S.L.	510	1235	530	1265	550	1295	570	1325	585	1350
		1000	530	1265	550	1295	570	1325	590	1360	610	1390
		2000	550	1295	570	1330	590	1360	610	1390	630	1425
		3000	570	1330	590	1360	615	1395	635	1430	655	1460
		4000	595	1365	615	1400	635	1430	660	1470	680	1500
		5000	615	1400	640	1435	660	1470	685	1510	705	1540
		6000	640	1435	660	1470	685	1510	710	1550	730	1580
		7000	665	1475	690	1515	710	1550	735	1590	760	1630
		8000	690	1515	715	1555	740	1595	765	1635	790	1675

Figure 5-11. Landing Distance